

It adopts optical bonding to prevent screen fogging, and has an automatic photosensitive probe built in, which supports automatic photosensitive adjustment and manual key adjustment. The LCD screen has a wide temperature and high brightness function, and the flat front panel is up to IP65 dustproof and waterproof, which can cope with the harsh outdoor environment with large temperature difference and high humidity.

## Features

- UV anti-ultraviolet touch screen.
- Optical Bonding Process.
- Adjustable Brightness.
- Intelligent heat dissipation control.
- Stable operation for a long time under high temperature and strong sunlight environment.



## Model

Product Size	10.1"
Non-touch	
Capacitive touch	
Resistive touch	

## I/O Interface



## Specifications

### Screen Parameter

LCD size	10.1" TFT LCD
Resolution	1280*800(16:10)
Viewing angle	80/80/80/80 (L/R/U/D)
Colour	16.7M
Brightness	1000 cd/m <sup>2</sup>
Contrast ratio	1000:1

### Touch Parameter


Touch type	Projection capacitive touch, 10-point multi touch	Resistive touch Single point	Non-touch
Light transmission	≥88%	≥78%	≥92%
Touch object	Handwriting or Capacitance pen	Fingertip or stylus	/
Controller	USB ( COM customized)	USB ( COM customized)	/

### Configuration

CPU	RTD2513	System language	Multilingual (default: English)
Hot key/button	AUTO/MENU/POWER/LEFT/RIGHT	Video input	PC-RGB:Format Up to 1920*1080@60HZ Color 16bit/24bit/32bit



## Dimensions



### Physical Characteristic

Overall dimensions	W293.6x H193.6x D62mm
Size of opening	W276.6 x H176.6mm

### Interface Parameter

Power interface1	1*Industrial terminal Support 12-36V wide voltage power supply
Power interface2	1*DC2.1, Support 12V-36V wide voltage power supply
HDMI	1*HDMI, Support HDMI data input, With a maximum of 1080P
Touch interface	1*TOUCH (RJ45)
VGA	1*VGA, Analog signal transmission
DVI	1*DVI, Digital signal transmission
Audio	1*Audio I/O, Support audio input and output
Brightness switch	Manual brightness and automatic brightness switch button
Ground column	Support(1*GND)

### Reliability Parameter

Working temperature	-20°C~70°C
Storage temperature	-30°C~80°C
Relative humidity	Humidity: 95% Non-Condensing
Waterproof grade	The front panel reaches IP65 protection level

### Power Parameter

Power input	DC 12V~36V
Power adapter	24V/2.5A