

**Data sheet**

IM 253DP, PROFIBUS-DP slave (253-1DP01)

## Technical data

<b>Order no.</b>	<b>253-1DP01</b>
Type	IM 253DP, PROFIBUS-DP slave
<b>General information</b>	
Note	-
Features	DC 24 V 12 Mbit/s Configuration via GSD-file of VIPA Up to 32 modules (16 analog) 244 Byte input and 244 Byte output data
<b>Technical data power supply</b>	
Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	70 mA
Current consumption (rated value)	1 A
Inrush current	65 A
$I^2t$	0.85 A <sup>2</sup> s
Max. current drain at backplane bus	3.5 A
Max. current drain load supply	-
Power loss	2.5 W
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	yes, parameterizable
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Supply voltage display	green LED
Service Indicator	-
Group error display	yes
Channel error display	none
<b>Hardware configuration</b>	
Racks, max.	1
Modules per rack, max.	32
Number of digital modules, max.	32
Number of analog modules, max.	16
<b>Communication</b>	
Fieldbus	PROFIBUS-DP to EN 50170
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Topology	Linear bus with bus termination at both ends
Electrically isolated	yes
Number of participants, max.	125

Node addresses	1 - 99
Transmission speed, min.	9.6 kbit/s
Transmission speed, max.	12 Mbit/s
Address range inputs, max.	244 Byte
Address range outputs, max.	244 Byte
Number of TxPDOs, max.	-
Number of RxPDOs, max.	-

### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Net weight	100 g
Weight including accessories	-
Gross weight	-

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL certification	yes
KC certification	-