

## Data sheet

### CP 341 (341-1AH01)

#### Technical data

<b>Order no.</b>	<b>341-1AH01</b>
Type	CP 341
<b>General information</b>	
Note	-
Features	RS232, isolated Function compatibility to Siemens CP 341 Parameterization via the Siemens parameterization package Data transfer rate up to 76.8 kbit/s Power supply via backplane bus
SPEED-Bus	-
<b>Current consumption/power loss</b>	
Current consumption from backplane bus	160 mA
Power loss	0.8 W
<b>Status information, alarms, diagnostics</b>	
Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	no
Diagnostics information read-out	possible
Supply voltage display	yes
Group error display	red SF LED
Channel error display	none
<b>Functionality Sub-D interfaces</b>	
Type	X2
Type of interface	RS232
Connector	Sub-D, 9-pin, male
Electrically isolated	yes
MPI	-
MP <sup>2</sup> I (MPI/RS232)	-
Point-to-point interface	yes
5V DC Power supply	-
24V DC Power supply	-
Type	-
Type of interface	-
Connector	-
Electrically isolated	-
MPI	-
MP <sup>2</sup> I (MPI/RS232)	-
Point-to-point interface	-

5V DC Power supply	-
24V DC Power supply	-

### Point-to-point communication

PtP communication	yes
Interface isolated	yes
RS232 interface	yes
RS422 interface	-
RS485 interface	-
Connector	Sub-D, 9-pin, male
Transmission speed, min.	-
Transmission speed, max.	76.8 kbit/s
Cable length, max.	15 m

### Point-to-point protocol

ASCII protocol	yes
STX/ETX protocol	yes
3964(R) protocol	yes
RK512 protocol	-
USS master protocol	-
Modbus master protocol	yes
Modbus slave protocol	yes
Special protocols	-

### Datasizes

Input bytes	16
Output bytes	16
Parameter bytes	(16 + 106)
Diagnostic bytes	4

### Housing

Material	PPE
Mounting	Rail System 300

### Mechanical data

Dimensions (WxHxD)	40 mm x 125 mm x 120 mm
Weight	170 g

### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

### Certifications

UL certification	yes
KC certification	yes