


2nd Gen Embedded Industrial monitor

It has 10.1" - 23.8" multiple sizes to choose from. The entire panel adopts 3mm ultra-thin panel that is more suitable for embedded installation, aluminum alloy structure, fanless totally enclosed design, and is equipped with self-developed industrial display drive board. The whole machine has low power consumption, good scalability, practicability, EMC compatibility and other performance, and is widely used in industrial control, military, communication, power, network, intelligent self-service terminal equipment and other automation applications.

Features >>



- The front frame is only 3mm thick, specially designed for embedded installation applications
- High precision die-casting aluminum molding, pure plane wire drawing process design, dustproof and waterproof
- Self developed display driver board, multiple touch modes available
- Industrial protection, applicable to various harsh environments
- Support VGA, HDMI, DVI and automatic identification of signal channels



ISO FC CE CCC RoHS 10 X

10.1"~23.8" optional

Product Model >>

Product size	Non-touch	Capacitive Touch	Resistive Touch	Resolution	Screen Scale	Brightness	Contrast ratio	Viewing Angle	Back Cover Style
10.1"				1280*800	16:10	300cd/m ²	1000:1	85/85/85/85 (L/R/U/D)	 (10.1-12.1 inch small back cover)
10.4"				1024*768	4:3	400cd/m ²	1000:1	80/80/80/60 (L/R/U/D)	
11.6"				1920*1080	16:9	300cd/m ²	1000:1	85/85/85/85 (L/R/U/D)	
12"				1024*768	4:3	500cd/m ²	1000:1	85/85/85/85 (L/R/U/D)	
12.1"				1280*800	16:10	300cd/m ²	1000:1	85/85/85/85 (L/R/U/D)	
13.3"				1920*1080	16:9	220cd/m ²	1000:1	85/85/85/85 (L/R/U/D)	 (13.3-23.8 inch large back cover)
15.6"				1920*1080	16:9	300cd/m ²	800:1	85/85/85/85 (L/R/U/D)	
15"				1024*768	4:3	300cd/m ²	1000:1	89/89/89/89 (L/R/U/D)	
17"				1280*1024	5:4	300cd/m ²	1000:1	85/85/80/70 (L/R/U/D)	
17.3"				1920*1080	16:9	300cd/m ²	600:1	80/80/60/80 (L/R/U/D)	
18.5"				1920*1080	16:9	300cd/m ²	1000:1	80/80/80/60 (L/R/U/D)	
19"				1280*1024	5:4	300cd/m ²	1000:1	85/85/80/80 (L/R/U/D)	
19.1"				1440*900	16:10	300cd/m ²	1000:1	80/80/80/80 (L/R/U/D)	
21.5"				1920*1080	16:9	300cd/m ²	1000:1	89/89/89/89 (L/R/U/D)	
23.8"				1920*1080	16:9	250cd/m ²	1000:1	89/89/89/89 (L/R/U/D)	

Product Installation >>



Product Specifications >>

Hardware Configuration	
CPU	RTD2513/RTD2556
Key functions	AUTO, MENU, POWER, LEFT, RIGHT
Menu language	Multi language (default English)
Video input	PC-RGB:Format Up to 1920*1080@60Hz
	PC-RGB:Color, 16bit, 24bit, 32bit
Touch Screen	
Capacitive Touch	Touch screen type: 10 point touch projection capacitive touch screen Light transmittance: ≥ 88% Input mode: handwriting or capacitive pen Controller communication: USB
Resistive Touch	Touch screen type: single point resistive touch screen Light transmittance: ≥ 78% Input mode: Fingertip or stylus Controller communication: USB
Non-touch	Light transmittance: ≥ 92%
Environmental	
Working Temperature	-10 °C ~60 °C
Storage Temperature	-20 °C ~ 70 °C
Relative Humidity	Humidity: 95% Non-Condensing
Vibration protection	IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
Impact protection	IEC 60068-2-27, half sine wave, duration 11ms
Product certification	CCC/CE/FCC/EMC/CB/ROHS
Other	
Input	12V-36V Power Input
Static power	18W
Fuselage Properties	Body material:aluminum alloy, body color: technical silver, classic gun black
Warranty Policy	Three years (one year free warranty)
Installation Method	Embedded installation is recommended, supporting wall mounted, desktop mounted, cantilever mounted, boom mounted, etc
I/O Interface	
Power interface	1*DC2.1 (DC 12-36V)
HDMI	1*HDMI , high-definition audio digital signal transmission, support HDMI data input, maximum support 1080F
VGA	1*VGA , Analog signal transmission, supporting the best resolution of VGA
DVI	1*DVI , digital signal transmission, supporting the best resolution of DVI digital signal
TOUCH	1*TOUCH, RJ45 interface standard (defined as USB), can be connected with capacitance/resistance touch
AUDIO I/O	1*AUDIO I/O, supporting audio input and output; Headphone stand: 3.5mm standard interface
GND	1*GND

Interface Distribution >>

